

Catering Hose assembly kits



Catering Hose

Under Control Instruments Catering gas hoses are designed for the rigours of an industrial commercial kitchen. As a leading supplier of parts and spares to the catering industry, we have a wealth of knowledge that has enabled us to develop and launch this new catering hose assembly kit. These parts are suitable for the harsh kitchen environments that exist and offer a long "fit and leave" working life.

They are available in several lengths, and sizes and are suitable for use with Natural and Propane gases (NG, LPG)

Catering hoses in commercial or industrial kitchen environments are subject to heat, oils, cleaning agents such as bleach, and constant movement due to cleaning regimes.

To handle these demanding requirements our catering hoses are made to BS 669 part 2 1997 so you can be assured that they will stand up to the duties and are fit for purpose.

Designed for gas-fired installations we offer the catering hose that incorporates the addition of stainless steel braiding. This feature gives added flexibility, and strength and allows more movement.

Each hose is fitted with a cleanable Yellow PVC sleeve that does not kink or slips down due to the design.

The hose is supplied with a quick fit/release brass coupling that allows for a quick connection or release. This provides a gas tight seal when disconnected from the appliance.


We supply each hose kit with a restraining cable set to protect the hose against damage if an appliance is moved as well as to protect the hose should the appliance fall over. The kit comprises of a PVC covered s.steel cable, two carabiner clips and a wall expanding bolt.

Features

- Approved to *BS 669 Part 2 1997*
- ½" & ¾" coupling end fitting and ½" & ¾" screwed Hex Male the other end.
- Quick release gas shut off brass coupling.
- Supplied with restraining kit.
- Suitable for natural gas or LPG.
- Stainless steel flexible high performance tube.
- Fitted in a wrinkle free PVC cover sleeve.

Materials

- Stainless steel corrugated tube with welded end fittings.
- Stainless steel braiding strengthening option.
- Quick release isolation coupling.
- Hexagon male stainless steel nipple.
- Cleanable wrinkle proof PVC sleeve.
- Restraining kit (PVC covered cable, clips and wall anchor bolts). *BS 669 Part 2 1997*



PARAMOUNT

| PART NO. | SIZE | LENGTH |
|-----------------|------|--------|
| GH121000 | ½" | 1000mm |
| GH121250 | ½" | 1250mm |
| GH121500 | ½" | 1500mm |
| GH341000 | ¾" | 1000mm |
| GH341250 | ¾" | 1250mm |
| GH341500 | ¾" | 1500mm |

Installation

Shall be in accordance with *BS 6173:1990*